

QC THIN-PAVE™ NI

STAMPABLE OVERLAY



■ QC THIN-PAVE NI stampable overlay transforms simple surfaces into attractive imprinted artwork.



■ Use the 42 standard colors or create a new color to design imprinted surfaces for the old-world look or hand-laid masonry.



■ Redress tired or plain concrete for a fraction of the cost associated with replacing existing flooring or paving.



STANDARD COLOR SELECTIONS

CUSTOM COLORS AVAILABLE UPON REQUEST

					
Coconut	Light Sand	Eggshell	Seashell	Latte	Golden Maple
					
Praline	Sable	Copper	Burnt Orange	Terra Cotta	Classic Beige
					
Moroccan Buff	Bisque Tan	Durango Tan	Toffee	Mesa Tan	Dark Granite
					
Cocoa Brown	Summer Beige	Hearth Stone	Cabaret Pink	Dusty Pink	Cork
					
Mesquite Brown	Mission Tile	Cortez Red	Chili Pepper	El Rancho Red	Comanche Red
					
Sky Blue	Slate Blue	Sand Dollar	Pinion Pine	Slate Green	Ireland
					
Pale Gray	Atlantic Gray	Flint Gray	Silver Gray	Basalt Gray	Stone Gray

Note: Colors Selections on this card provide a close approximation to the actual appearance of QC product color when used on horizontally troweled and/or imprinted concrete that has been sealed. Variations can be expected due to job conditions, finishing techniques, method of cure and use of sealers.

Please refer to price list for color groups and pricing. Custom colors and color matches are available: A minimum quantity or nominal charge may be required. Please contact QC Customer Service for a price quote.

Color Chart 14.3.1105C
For Professional Use Only



*Manufacturer of
Premium Architectural
Concrete Products*

COLOR SELECTION GUIDE



QC THIN-PAVE™ NI*

STAMPABLE OVERLAY

- **COLOR THAT PERFORMS:** QC THIN-PAVE NI stampable overlay transforms almost any simple flooring into an appealing expanse of imprinted artwork.
- **MADE TO ORDER:** Available in 42 standard colors and an endless array of personalized colors, QC THIN-PAVE NI always makes each job unique and impressive.
- **DESIGNED FOR CRAFTSMANSHIP:** Created to bond with most structurally sound substrates, QC THIN-PAVE NI can be textured from 1/4" to 5/8" thick with most standard imprinting tools for the illusion of authentic, hand-laid stone or brickwork.
- **BUILT FOR DURABILITY:** Convert tired or plain concrete into stunning, stamped paving. QC THIN-PAVE NI allows a limitless variety of options to fit any design criteria.
 - **COVERAGE RATES†:** approximately 22 square feet at 1/4", 16 square feet at 3/8", 11 square feet at 1/2" and 9 square feet at 5/8".
†Recommended thickness rate for QC THIN-PAVE NI is 3/8".
 - **PACKAGE SIZES:** Liquid: 1- and 5-gallon pails.
Powder: 47-lb. bags.
 - **RECOMMENDED SEALERS:** QC CemSeal*, QC PermaSeal*, QC Solvent-Based Sealers* or QC Surpro (SB or WB)*.
- QC THIN-PAVE NI is a two-component polymer modified cementitious stampable overlay. When applied in conjunction with color, stains and sealers, QC THIN-PAVE NI can produce a decorative paving finish similar to imprinted concrete.
- QC THIN-PAVE NI is environmentally safe, virtually odorless, and easy to install. It requires no special training for installation by a crew experienced in the application of similar materials and is easily handled by a handyman or mason. It sets rapidly, can be applied over damp (not wet) surfaces and can be installed at temperatures as low as 55 °F.
- QC THIN-PAVE NI can be utilized in new construction or renovation and provides a fast track construction option by allowing the delay of decorative flooring installation until after the initial heavy construction is complete. This eliminates the need to invest in protection of the decorative surface and greatly reduces damage from construction related traffic.
- QC THIN-PAVE NI Tint Packs can be added to integrally color the material before application. Colors are designed to approximate color samples shown on the QC COLOR HARDENER* and QC COLORTECH – E* color charts.
- QC THIN-PAVE NI has very high compression strength and can be left exposed to traffic; regular maintenance is recommended. The system consists of a wet primer application, pigmented latex modified mortar, QC RELEASE AGENT, and QC SEALERS. When required, QC PATINA STAIN* and QC CEMENTINT* can be applied. Most imprinting tools can be used with QC THIN-PAVE NI.

*PLEASE REFER TO THE CORRESPONDING PRODUCT INFORMATION BULLETINS FOR TECHNICAL AND APPLICATION DATA.

www.qcconstructionproducts.com

For complete information on all QC products — including product information catalogs, product brochures, color charts, technical specifications, sales aids and more — contact QC CONSTRUCTION PRODUCTS.

QC CONSTRUCTION PRODUCTS® is a registered trademark and servicemark with the U.S. Patent Office and other countries.

© 2005 QC CONSTRUCTION PRODUCTS Printed in U.S.A. 11.05 20M

QC CONSTRUCTION PRODUCTS

11901 Gavin Rd • Laredo, TX 78045
Customer Service 800.453.8213

www.qcconstructionproducts.com ■ District sales offices and warehouses nationwide

QC CONSTRUCTION PRODUCTS available through: