



HEALTH	2
FLAMMABILITY	2
PHYSICAL HAZARD	0
PERSONAL PROTECTION	В

### Section I - Product Identification

Product Name:	QC SURPRO 100LV PART A		
Company	QC Construcion Products 11901, Gavin Rd, Laredo Tx, 78045		
Chemical Name:	N/A		
Chemical Family:	N/A		
Chemical Formula:	Proprietary		
D.O.T. Hazard Class:	Paint, 3, UN, 1263, III (Flash point greater than 73 F)		
Appearance & Odor:	Clear liquid, sweet odor		
Emergency Telephone Number:	CHEMTREC (800) 424-9300		
Telephone Number for Information:	956 622 7677		
Product Use:			

## Section II - Hazards Identification

Hazard Symbol:





#### **Hazard Statements**

Flammable Liquid and Vapor Causes mild skin irritation Causes serious eye irritation Harmful if inhaled May cause respiratory irritation

May cause respiratory irritation
May cause drowsiness or dizziness

## **Precautionary Statements**

Obtain special instructions before use.

Keep away from heat/sparks/open flames /hot surfaces. No smoking.

Take precautionary measures against static discharge.

Wear respiratory protection/protective gloves/protective clothing/eye protection/face protection.

Do not breathe mists, vapors or spray.

IF IN EYES: Rinse with water for several minutes. Remove contact lenses, if present and easy to do. If irritation

occurs and persists, get medical attention.

IF ON SKIN: Remove immediately all contaminated clothing. Rinse skin with water for several minutes. Wash

contaminated clothing before reuse. If irritation occurs and persists, get medical attention.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention

immediately.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Immediately call a physician or poison center.

Keep container tightly closed. Store in a well ventilated place. Dispose of contents/container in accordance with local regulation.

### Section III - Product Composition

Composition	CAS Number	Weight %
PARACHLOROBENZOTRIFLUORIDE	98-56-6	70 - 75
HEXYLENE GLYCOL	107-41-5	2 - 7
N-BUTYL ACETATE	123-86-4	1 - 3

### Section IV - First Aid Measures

**Eye Contact:** Rinse with water for 15 minutes. Remove contact lenses, if present and easy to do. If irritation occurs and persists, get medical attention.

**Skin Contact:** Remove immediately all contaminated clothing. Rinse skin with water for several minutes. Wash contaminated clothing before reuse. If irritation occurs and persists, get medical attention.

**Inhalation:** Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention immediately. Administer oxygen or artificial respiration as necessary.

Ingestion: Rinse mouth. Do NOT induce vomiting. Immediately call a physician or poison center.

## Section V - Fire Fighting Measure

Unusual Fire Explosion Hazards: In poorly ventilated areas, vapors may accumulate and travel to locations distant to the work

area. Be aware of any flame or spark sources which could ignite vapors near and in range of

the work area.

Fire Extinguishing media: Hazards during fire-fighting:

Use dry chemical, carbon dioxide or alcohol-resistant foam. Containers may rupture when exposed to extreme heat.

Protective equipment for fire-fighting:

Wear NFPA-approved self-contained breathing apparatus, helmet, hood, boots and gloves.

### Section VI - Accidental Release Measures

### Personal precautions:

Use recommended personal protective clothing and equipment, including eye protection, chemically resistant gloves and vapor respirator. To prevent slipping, do not walk through spilled material.

### **Environmental precautions:**

Follow all Federal, State and Local regulations when storing and disposing of substances. Do not allow material to run off of work area, and material should be absorbed, collected and disposed of in accordance with regulations. Keep product from entering storm drains. Consult local and federal guidelines for proper disposal of these materials.

#### Cleanup:

General: In poorly ventilated areas, vapors may accumulate and travel to locations distant to the work area. Be aware of any flame or spark sources which could ignite vapors near and in range of the work area. Eliminate all ignition sources in the immediate area. Use clean non-sparking tools for spill cleanup.

- For small amounts of released material: Absorb or cover with inert absorbent, sand or dry earth. Transfer to a metal or HDPE container for disposal. - For large amounts of released material: Dike around spilled material with absorbent to contain. Absorb or cover with inert absorbent, sand or dry earth. Transfer to a metal container for disposal..

### Section VII - Handling and Storage

#### Handling:

General advice - No specific measures are necessary provided product and recommended protective clothing/equipment are used correctly. Do not generate and breathe mists, vapors or fine spray. May only be mixed with Surtec Surpro 100LV Part B. Do not mix with other chemicals. This is a commercial product, not intended for home use. Keep out of reach of children.

#### Storage:

General advice - Protect against physical damage. Store in a cool, well ventilated area. Store in a tightly closed container.

#### Shelf Life:

12 months minimum

### Section VIII - Exposure Controls / Personal Protection

#### Personal Protective Equipment



### Advice on system design:

Provide local exhaust ventilation to control vapors for published exposure limits.

Personal protective equipment (HMIS rating 'I'):

Eye protection: Wear safety glasses with side shields or safety goggles to prevent exposure or full face shield if splash hazard exists. Skin protection: Chemical-resistant gloves. Wear appropriate protective clothing to prevent possible skin contact.

Respiratory protection: Product, as supplied, is not intended for airless or other paint spray application. Do not breathe mists, vapors or spray. Use proper NIOSH-OSHA respirator fitted with proper cartridges if mists are generated, ventilation is inadequate or exposure limits are exceeded.

## Section VIII - Exposure Controls / Personal Protection

General safety and hygiene measures: Exercise stringent hygiene practices to minimize exposure. If contact occurs, wash any body part with soap and water immediately. Wash hands after use, and before eating, drinking or smoking. Other protective measures:

Nearby running water on the job site is necessary, should an accident occur.

Exposure Guidelines:

ACGIH TLV: 150 ppm (123-86-4) STEL: 200 ppm (123-86-4) OSHA PEL: 150 ppm (123-86-4)

## Section IX - Physical and Chemical Properties

Appearance: Clear Liquid Flash Point: 115° F C.O.C.

Odor: Upper/Lower Flammability Limits: No information available

pH value: No information available Relative Density (water): 1.25

1.25 (H2O = 1)Auto-Ignition Temperature: No information available Specific gravity: No information available Decomposition temperature: Solidification temperature: No information available Freezing/Melting point: No information available Partition Coefficient No information available Boiling point: No information available Odor Threshold No information available

Vapor density: No information available Viscosity: ~200 cps.

Vapor pressure: No information available Partition Coefficient: No information available

Evaporation Rate: No information available Solubility in water: None

Regulatory VOC: <100 g/l

### Section X - Reactivity / Estability

Conditions to avoid: Heat, flame, sparks. Substances to avoid: Oxidizers, water.

Hazardous reactions: Product is stable under normal conditions of use and storage.

Decomposition or By-products: In fire conditions: carbon monoxide (CO), carbon dioxide (CO2), fluorine, chlorine.

## Section XI - Toxicological Information

#### **Acute Toxicity (Symptoms):**

**Oral:** Ingestion may cause pain, nausea, vomiting, and diarrhea.

Eye irritation: Irritation, redness, tearing and swelling. May cause temporary corneal injury.

**Skin irritation:** Irritation, redness, itching and swelling.

Inhalation: Inhalation of vapors may cause irritation to the respiratory tract with runny nose, sore throat, coughing

and difficulty breathing.

Sensitization: Skin: No. Respiratory: No

Target Organ Effects - Single Exposure: (Respiratory System): May cause respiratory irritation; (Central

Nervous System): May cause drowsiness or dizziness.

**Carcinogenicity:** No carcinogenic substances as defined by ACGIH, IARC, NTP and/or OSHA.

### Section XII - Ecological Information

Biodegradation: Environmental toxicity:

Test method: Unspecified Acute and prolonged toxicity to fish: Not available

Analysis method: Unspecified Toxicity to microorganisms: Not available

Degree of elimination: Not readily biodegradable.

Other ecotoxicological information: Not available

## Section XIII - Disposal Considerations

Waste disposal of substance: Dispose of in accordance with all Federal, State and Local regulations when storing

and disposing of substances. It is the waste generator's responsibility to determine if a particular waste is hazardous under RCRA (EPA regulations for hazardous waste).

Container disposal: Dispose of in a licensed facility in accordance with local regulations.

RCRA: Unspecified.

## Section XIV - Transportation / Shipping Data

DOT:

UN/ID No: 1263

Proper Shipping Name: PAINT (FLASH POINT > 73°F)

Hazard Class: 3 Packing Group: III

## Section XV - Regulatory Information

**Federal Regulations:** 

Registration status:

TSCA, US: All components are listed or exempt.

SARA hazard category (EPCRA 311/312): Fire hazard

Acute health hazard

**SARA TITLE III, SECTION 313:** 

CAS Number: Chemical Name:

None

**State Regulations:** 

Chemicals known to the State of California to cause cancer, birth defects or other reproductive harm

CAS Number: Chemical Name:

None

## Section XVI - Other Information

HMIS Rating:

 HEALT
 2
 0 = Minimum

 FLAMMABILITY
 2
 1 = Slight

 REACTIVITY
 0
 2 = Moderate

 PPE
 3 = Serious

#### **Further information:**

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

#### Legend

ACGIH - American Conference of Governmental Hygienists

CERCLA - Comprehensive Environmental Response, Compensation, and

Liability Act

RCRA - Resource Conservation and Recovery Act

DOT - Department of Transportation DSL - Domestic Substance List

EPA - Environmental Protection Agency

HMIS - Hazardous Materials Information System

IARC - International Agency for Research on Cancer

MSHA - Mine Safety Health Administration

NDSL - Non-Domestic Substance List

NIOSH - National Institute for Occupational Safety and Health

NTP - National Toxicology Program

WHMIS - Workplace Hazardous Materials Information

System

PEL - Permissible Exposure Limit

RTK - Right To Know

SARA - Superfund Amendments and Reauthorization Act

STEL - Short Term Exposure Limit TLV - Threshold Limit Value

TSCA - Toxic Substances Control Act

TWA - Time Weighted Average

V - Volume

VOC - Volatile Organic Compound

OSHA - Occupational Safety and Health Administration

#### References:

CA: California

CAS: Chemical Abstract Services

CERCLA: Comprehensive Environmental Response,

Compensation, and Liability Act of 1980 CFR: Code of Federal Regulations DOT: Department of Transportation

EINECS: European Inventory of Existing Commercial

chemical Substances

ENCS: Existing and New Chemical Substances IARC: International Agency for Research on Cancer

IBC: Intermediate Bulk Container

IECSC: Inventory of Existing Chemical Substances IMDG: International Maritime Dangerous Goods

Inh: Inhalation

IOC: Inventory of Chemicals

KECI: Korean Existing Chemicals Inventory KECL: Korean Existing Chemicals List

LC: Lethal Concentration LD: Lethal Dose MA: Massachusetts MN: Minnesota N/Ap: Not Applicable

N/Av: Not Available

NIOSH: National Institute of Occupational Safety and Health

NJ: New Jersey

NOEC: No observable effect concentration NTP: National Toxicology Program

OSHA: Occupational Safety and Health Administration

PEL: Permissible exposure limit

PICCS: Philippine Inventory of Chemicals and Chemical Substances

RCRA: Resource Conservation and Recovery Act

RTECS: Registry of Toxic Effects of Chemical Substances SARA: Superfund Amendments and Reauthorization Act

STEL: Short Term Exposure Limit

TDG: Canadian Transportation of Dangerous Goods Act & Regulations

TLV: Threshold Limit Values TWA: Time Weighted Average TSCA: Toxic Substance Control Act

WHMIS: Workplace Hazardous Materials Identification System

1. ACGIH, Threshold Limit Values for Chemical Sunstances and Physical Agents & Biological Exposure Indices for 2015.

2. International Agency for Research on Cancer Monographs, searched 2015.

3. Canadian Centre for Occupational Health and Safety, CCInfoWeb Databases, 2015 (Chempendium, HSDB, RTECs).

4. Material Safety Data Sheet from manufacturer.

5. OECD - The Global Portal to Information on Chemical Substances - eChemPortal,

2015.

5. US EPA Title III List of Lists

6. California Proposition 65 List

#### **DISCLAIMER**

This Safety Data Sheet was prepared by JBM Inc. using information provided by "QC" CONSTRUCTION PRODUCTS QUALITY ARCHITECTURAL CONCRETE. The information in the Safety Data Sheet is offered for your consideration and guidance when exposed to this product.

JBM Inc. and "QC" CONSTRUCTION PRODUCTS QUALITY ARCHITECTURAL CONCRETE expressly disclaim all expressed or implied warranties and assume no responsibilities for the accuracy or completeness of the data contained herein. The data in this SDS does not apply to use with any other product or in any other process.

This Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of JBM Inc. and "QC" CONSTRUCTION PRODUCTS QUALITY ARCHITECTURAL CONCRETE.

Before using this product:

Complety read the QC Tech-Data Bulletin Antiquing Release and the product label.

10.05M

QC Surpro 100LV Part A